

Semi Synthetic Engine Oil – High Quality

Power Synth S

SAE 10W30/10W40



API: SN

Product Description

Power Synth S is a blend of high quality base stocks and exclusive high performance additive package that ensures minimum wear, extended engine life, longer oil life and easy cold weather starting. It enhances the engine performance and can be used for all high performance gasoline engine cars equipped with direct-injection, multi – valve, and turbo charged technologies, designed to improve the fuel economy efficiency.

Benefits

Power Synth S provides the following benefits when used as recommended:

- High fluidity at low temperature and excellent cold start
- Great durability at high temperature
- Excellent high temperature protection
- Prolong engine life by reducing wear
- Excellent low temperature properties
- Prolonged oil change interval & keeps engine clean
- Protects against rust & wear

Typical Characteristics

Power Synth	10W40	10W30	Credentials & Specifications
API Grade	SN	SN	API: SN/SM/SL/SJ/CF
Specific Gravity @ 15°C	0.8620	0.8600	Ford WSS M2 C 917 A
Flash Point, °C	232	228	ACEA: A3/B3/B4
Pour Point, °C	- 30	-33	VW 505.01, 505.00, 500.00
Viscosity at 40°C, cSt	95.0	75.0	
Viscosity at 100°C, cSt	14.0	11.75	
Viscosity Index	150	150	
Total Base No., Min.	8.50	8.50	
CCS Viscosity cP at -25°C	6250	6200	

Typical physical characteristics of Power Synth S are given in the table. These are intended as a guide to the industry and are not necessarily manufacturing or marketing specifications.

Health and Safety

Detailed health and safety information for this product is provided in a Material Safety Data Sheet which is available upon request from your Emarat lubricants sales office, or via the Internet on www.emarat.ae